



AUFSTECK- STROMWANDLER

Aufsteckwandler
40 bis 250A
Kabel Ø 15
Schiene 15x3



Stromwandler, Typ TR 0

Primary current	Class	Power	Secondary current	Secondary current	Weight
A		VA	5A	1A	Kg
40	3	2	TR0-040A5-3-2VA	TR0-040A1-3-2VA	0,25
50	3	2	TR0-050A5-3-2VA	TR0-050A1-3-2VA	0,25
60	3	3	TR0-060A5-3-3VA	TR0-060A1-3-3VA	0,25
75	3	3	TR0-075A5-3-3VA	TR0-075A1-3-3VA	0,25
80	3	3	TR0-080A5-3-3VA	TR0-080A1-3-3VA	0,25
100	1	3	TR0-100A5-1-3VA	TR0-100A1-1-3VA	0,25
120	1	3	TR0-120A5-1-3VA	TR0-120A1-1-3VA	0,25
125	0.5	3	TR0-125A5-0.5-3VA	TR0-125A1-0.5-3VA	0,25
150	0.5	3	TR0-150A5-0.5-3VA	TR0-150A1-0.5-3VA	0,25
200	0.5	3	TR0-200A5-0.5-3VA	TR0-200A1-0.5-3VA	0,25
250	0.5	5	TR0-250A5-0.5-5VA	TR0-250A1-0.5-5VA	0,25

Abmessungen

