



Hermetically sealed plug in relays, Harmony, 5A, 4 CO, 120V AC

782XDXH21-120A

Product range	Harmony Electromechanical Relays
Product type	Plug-in relay
[In] rated line current	5 A
Contact composition	4 C/O
Contacts material	Silver alloy contacts
Cover options	Hermetically sealed
Series name	Miniature
[Uc] control circuit voltage	120 V

Complementary

Class number	782H
Maximum switching voltage	240 V AC
[le] rated operational current	5 A at 120 V AC (on resistive load) 5 A at 240 V AC (on resistive load) 5 A at 30 V DC (on resistive load)
Coil resistance	3900 Ohm
Connections - terminals	Plug in
Minimum switching current	500 mA at 12 V AC 500 mA at 12 V DC
Average coil consumption	1.20 VA
Electrical durability	100000 cycles resistive load conforming to IEC
Mechanical durability	10000000 cycles
Response time	20 ms
Dielectric strength	1600 V AC between coil and contact 1600 V AC between poles
Net weight	45 g

Environment

Shock resistance	10 gn
Environmental characteristic	Hazardous location T5 40 °C tests
Vibration resistance	6 gn (f = 1055 Hz)


Ambient temperature range - operational	-4570 °C
Ambient air temperature for storage	-6085 °C
Product certifications	UL CSA CE
Height	32.5 mm
Width	22.75 mm
Depth	28.75 mm
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.875 cm
Package 1 Width	2.275 cm
Package 1 Length	2.875 cm
Package 1 Weight	45.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	3.0 cm
Package 2 Width	11.0 cm
Package 2 Length	13.0 cm
Package 2 Weight	450.0 g
Unit Type of Package 3	CAR
Number of Units in Package 3	100
Package 3 Height	18.0 cm
Package 3 Width	25.8 cm
Package 3 Length	33.5 cm
Package 3 Weight	5.4 kg
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Product data sheet

782XDXH21-120A

Dimensions Drawings

Dimensions




(A): 0.312 (7.92) LONG #3-48 THREAD

Product data sheet

782XDXH21-120A

Connections and Schema

Wiring



Recommended replacement(s)