

OFFER NO. :	12/09/2016	DATE OF DOC. :	12/09/16
	1617/2016 POS. 1		
PRODUCT CODE :	P38706100100625		
D.C. MOTOR TYPE :	P 132 X 2 - 06 PVA/1001		
QUANTITY :	1	DELIVERY TIME:	0
BUYER :	IMPEXRON GMBH		



SC/MR

**ELECTRICAL DATA**

POWER (KW) :35,00/  
 ARM. VOLT. (V) :440,00/  
 SPEED (RPM) :2050/  
 ARM. CURR. (A) :

DUTY : S1  
 SUPPLY : T.F.C.B.  
 ECCITAZ. : SEPARATE WITHOUT STAB.SERIES

NO. OF POLES : 4

INS. CLASS : H DT H  
 FIELD VOLT(V): 190,00/0,00

**MECHANICAL DATA**

ENVIRONMENT : NORMAL ENVIRONMENT  
 MOUNTING (IM) : 1001 B3  
 PROTECTION (IP) : 23 S  
 FAN SUPPLY : 240/415V +/-5% 50HZ TRIPHASE  
 DIRECT COUPLING  
 VIBRATION GRADE : N  
 SHAFT MATERIAL : STANDARD  
 D.E. SHAFT : STANDARD DIAM. (MM) : 38 k6  
 D.E BEARING : BALL

ALTITUDE (MT.) : 1000

COOLING (IC) : 06 PVA

TROPICALISATION

LENGTH (MM) : 80 WITH KEY

COOLER MOUNTING : TOP  
 TERMINAL BOX : STANDARD - RIGHT

PAINTING : STANDARD - CYCLE N. 1  
 RAL : 6011

**INCORPORATED ACCESSORIES**

THERMAL PROTECTION: 1+1-KLIXON MAIN/AUX. POLES  
 FILTER

PRESSURE SWITCH

**ACCESS. PROVISIONS**

PROVISION FOR TACHO/ENCODER: REO 444 R D.14/11 AND EQUIVAL.

TACHOG./ENCODER : REO 444R1-60 V/1000 RPM D11  
 BRAKE : NIA 6,3 (63 Nm) 24V DC WITH CABLE  
 TACHOPROVISION ON BRAKE

- SUPPLY -  
 - SUPPLY -

**GENERAL DATA**

REFERENCE TEMP. : 45 C.

ELECTRIC STANDARDS. : CEI,IEC  
 NAMEPLATE : ENGLISH  
 NDE BEARING : 6308-2Z/C3  
 MOMENT OF INERTIA J (KGM2) :0,1150

D.E. BEARING : 6310-2Z/C3  
 TOTAL WEIGHT (KG) : 185,00  
 DYNAMIC LOAD OF SHORT CIRCUIT (KG) :770  
 PACKING : ON PALLET

**NOTES**

INTERCHANGEABLE TO 1468/89