
DO NOT SCALE PRINT








CONTACT SETTING SCREW PG 16 for cable size: Ø12,5-Ø15 mm -VENTILATION \_N 17 mm

Scale Range: -1,0 to 1,0 bar. indication accuracy: +/- 1,5% Contact Accuracy: +/-2,0% Ambient temperature -40° to 70°C Outdoor mounting, protetion class IP54. Casing: Stainless Steel-Polycarbonate UV stabilized. Contact capacity: 110 VDC, 0,1 A. Insulation test 2 kV, 50 Hz, 60 sec.



Switch Operation: Common and L2 are normally closed. On decreasing pressure/increasing vacuum, common opens on L2 at the L2 setpoint and re-closes when pressure rises/vacuum decreases between L2 and L2+0,2 Bar.

Common and L1 are normally open. On increasing pressure/decreasing vacuum, common closes on L1 at the L1 setpoint and re-opens when pressure falls/vacuum increases between L1 and L1-0,2 Bar.

	NOTICE
THE	DRAWING IS THE PROPERTY OF QUARTROL COMPANY LLC
	IS LOANED ONLY ON THE CONDITION THAT IT WILL BE USED
	FACILITATE THE PURPOSE FOR WHICH IT WAS INTENDED
ANE	NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED O
	IS NOT TO BE USED IN WHOLE OR PART FOR FURNISHING
INFO	DRMATION RELATIVE TO THE MAKING OF DRAWINGS, PARTS,
APF	ARATUS OR PARTS THEREOF, EXCEPT BY WRITTEN ORDER
FRC	M QualiTROL COMPANY LLC.

10-469 REV. E 04/06/06   DRAWN EN DATE 124/									
1 0-469 REV. E 04/06/06 DRAWN EN DATE					DATE				
LET	DATE	ALTERATION				C.N.	rinion.		
2	6-17-2003	REDRAWN; ELECTRIC SYMBOL CHANGED				PL	FINISH:		
-	8-13-13	Redrawn; Add switch operation notes				31609			
							MATERIAL:	IAI :	
							Р	RESSURE MONITOR	
							TITLE:		

FAIRPORT, NEW YORK

1 OF 2 NTS 48432-1

48432-1

